

Garant
GARANT Master Form Steel fluteless machine tap with oil grooves HSS-E-PM, TiAlN, MF: 6X0,75

Order data

Order number	139280 6X0,75
GTIN	4062406383848
Item class	11I

Description
Version:
GARANT Master Form Steel:

The latest generation of **high-performance fluteless taps** are specially developed for **use in steels**.

- **Optimised polygon geometry for a reduced torque.**
- **Multi-layer HIPIMS coating for high wear resistance.**
- **HSS-E-PM substrate for top process reliability.**

DIN 2174 ($\approx$ DIN 371) $\leq$ M10; DIN 376 $\geq$ M12).

Tolerance class: ISO 2X 6HX

Thread pitch: 0.75 mm

Overall length L: 80 mm

Shank $\varnothing D_s$: 6 mm

Shank square $\square$: 4.9 mm

Tapping hole $\varnothing$ guide value: 5.65 mm

Technical description

Shank $\varnothing D_s$	6 mm
Thread depth	18 mm
Number of cutting edges Z	5
Thread pitch	0.75 mm
Overall length L	80 mm

Tolerance class	ISO 2X 6HX
Thread Ø	6 mm
Series	GARANT Master Steel
Tapping hole Ø guide value	5.65 mm
Thread size	M6×0.75
Shank square □	4.9 mm
Number of clamping slots	5
Coating	TiAlN
Thread type	MF
Flank angle	60 degrees
Tool material	HSS E PM
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Colour ring	without
Type of product	Fluteless tap