

Garant
GARANT Master TM plain shank thread mill 2.5×D, TiAlN, M: M3

Order data

Order number	139641 M3
GTIN	4062406240813
Item class	11D

Description
Version:

Solid carbide thread milling cutters **with irregular cutting edge spacing and an increased number of cutting edges**. Due to the **irregular cutting edge spacing** they achieve **very smooth running** and **long tool life**.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- **Significantly reduced vibration due to irregular cutting edge spacing**
- **Increased number of cutting edges**
- **New coating for optimum wear resistance**
- **Corrected thread profile for avoidance of profile distortions**

Through-coolant feed ≥ M4

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 139640 / 136941 + 129100 HB**

Form **HE**: order with **No. 139640 / 136941 + 129100 HE**.

Through-coolant: no

No. of teeth Z: 4

Thread pitch: 0.5 mm

Nominal Ø D_C: 2.33 mm

maximum insertion depth L₁: 7.73 mm

Shank length L_s: 36 mm

Overall length L: 58 mm

Shank Ø D_s: 6 mm

Technical description

Thread Ø	3 mm
----------	------

Thread size	M3
Thread pitch	0.5 mm
Number of clamping slots	4
Feed f_z in steel < 750 N/mm ²	0.01 mm
maximum insertion depth L_1	7.73 mm
Thread depth	6 mm
Shank length L_s	36 mm
No. of teeth Z	4
Through-coolant	no
Overall length L	58 mm
Shank Ø D_s	6 mm
Nominal Ø D_c	2.33 mm
Coating	TiAlN
Thread type	M
Thread type	M-LH
Flank angle	60 degrees
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA to h6
Application for type of drilling	up to 2.5×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Shank tolerance	h6
Colour ring	green
Internal/external application	Internal
Series	GARANT Master TM
Type of product	thread milling cutter

Services

129100 HE

Shank grinding Type HE	
Shank grinding Type HB	129100 HB