

GARANT Master TM plain shank thread mill 2.5×D, TiAIN, M: M4



Order data

Order number	139641 M4
GTIN	4062406240820
Item class	11D

Description

Version:

Solid carbide thread milling cutters with irregular cutting edge spacing and an increased number of cutting edges. Due to the irregular cutting edge spacing they achieve very smooth running and long tool life.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- · Significantly reduced vibration due to irregular cutting edge spacing
- · Increased number of cutting edges
- New coating for optimum wear resistance
- · Corrected thread profile for avoidance of profile distortions

Through-coolant feed ≥ M4

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 139640 / 136941 + 129100 HB**Form **HE**: order with **No. 139640 /136941 + 129100 HE**.

Through-coolant: yes

No. of teeth Z: 4 Thread pitch: 0.7 mm Nominal \varnothing D_c: 3.1 mm

maximum insertion depth L₁: 10.13 mm

Shank length L_s: 36 mm Overall length L: 58 mm Shank Ø D.: 6 mm

Technical description

Feed f_z in steel < 750 N/mm² 0.02 mm

Thread depth	8 mm
Through-coolant	yes
Shank length L _s	36 mm
Thread Ø	4 mm
No. of teeth Z	4
Number of clamping slots	4
maximum insertion depth L ₁	10.13 mm
Thread size	M4
Shank Ø D _s	6 mm
Thread pitch	0.7 mm
Overall length L	58 mm
Nominal Ø D _c	3.1 mm
Coating	TiAIN
Thread type	M
Thread type	M-LH
Flank angle	60 degrees
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA to h6
Application for type of drilling	up to 2.5×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Shank tolerance	h6
Colour ring	green
Internal/external application	Internal
Series	GARANT Master TM
Type of product	thread milling cutter

Services

129100 HB

Shank grinding Type HB	
Shank grinding Type HE	129100 HE