

Garant
GARANT Master TM plain shank thread mill 2×D, TiAlN, UNC: 10-24

Order data

Order number	139722 10-24
GTIN	4062406057923
Item class	11D

Description
Version:

Solid carbide thread milling cutters **with irregular cutting edge spacing and an increased number of cutting edges**. Due to the **irregular cutting edge spacing** they achieve **very smooth running** and **long tool life**.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- **Significantly reduced vibration due to irregular cutting edge spacing**
- **Increased number of cutting edges**
- **New coating for optimum wear resistance**
- **Corrected thread profile for avoidance of profile distortions**

Application:

For **UNC unified coarse threads** ASME-B1.1.

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 139722 + 129100 HB**

Form **HE**: order with **No. 139722 + 129100 HE**

Spacing of the cutters: unequal spacing

Thread type: UNC

Thread type: UNC-LH

No. of teeth Z: 4

Threads per inch: 24

Nominal $\varnothing D_c$: 3.55 mm

Flute length L_c : 10.02 mm

Shank length L_s : 36 mm

Overall length L: 58 mm

Shank $\varnothing D_s$: 6 mm

Technical description

Thread pitch	1.058 mm
Thread Ø	4.83 mm
Shank length L _s	36 mm
Threads per inch	24
Overall length L	58 mm
No. of teeth Z	4
Number of clamping slots	4
Thread type	UNC
Thread type	UNC-LH
Shank Ø D _s	6 mm
Full profile	yes
Flute length L _c	10.02 mm
Feed f _z in steel < 750 N/mm ²	0.03
Thread size	10-24 UNC
Nominal Ø D _c	3.55 mm
Series	GARANT Master TM
Coating	TiAlN
Flank angle	60 degrees
Tool material	solid carbide
Shank	DIN 6535 HA with h6
Through-coolant	yes
Cutting direction	right-hand
Application for type of drilling	up to 2×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Shank tolerance	h6
Colour ring	green
Internal/external application	Internal

Type of product

thread milling cutter