

Garant
GARANT Master TM plain shank thread mill 2xD, TiAlN, UNC: 9/16-12

Order data

Order number	139722 9/16-12
GTIN	4062406057985
Item class	11D

Description
Version:

Solid carbide thread milling cutters **with irregular cutting edge spacing and an increased number of cutting edges**. Due to the **irregular cutting edge spacing** they achieve **very smooth running** and **long tool life**.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- **Significantly reduced vibration due to irregular cutting edge spacing**
- **Increased number of cutting edges**
- **New coating for optimum wear resistance**
- **Corrected thread profile for avoidance of profile distortions**

Application:

For **UNC unified coarse threads** ASME-B1.1.

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 139722 + 129100 HB**

Form **HE**: order with **No. 139722 + 129100 HE**

Spacing of the cutters: unequal spacing

Thread type: UNC

Thread type: UNC-LH

No. of teeth Z: 6

Threads per inch: 12

Nominal Ø D_C: 11.6 mm

Flute length L_C: 28.51 mm

Shank length L_S: 45 mm

Overall length L: 92 mm

Shank Ø D_S: 12 mm

Technical description

Thread pitch	1.16 mm
Threads per inch	12
Overall length L	92 mm
Number of clamping slots	6
Shank Ø D _s	12 mm
Thread type	UNC
Thread type	UNC-LH
No. of teeth Z	6
Shank length L _s	45 mm
Thread Ø	14.29 mm
Full profile	yes
Flute length L _c	28.51 mm
Feed f _z in steel < 750 N/mm ²	0.1
Thread size	9/16-12 UNC
Nominal Ø D _c	11.6 mm
Series	GARANT Master TM
Coating	TiAlN
Flank angle	60 degrees
Tool material	solid carbide
Shank	DIN 6535 HA with h6
Through-coolant	yes
Cutting direction	right-hand
Application for type of drilling	up to 2xD for blind holes and through holes
Spacing of the cutters	unequal spacing
Shank tolerance	h6
Colour ring	green
Internal/external application	Internal

Type of product

thread milling cutter