

Garant
GARANT Master TM plain shank thread mill 2×D, TiAlN, UNF: 7/16-20

Order data

Order number	139727 7/16-20
GTIN	4062406058067
Item class	11D

Description
Version:

Solid carbide thread milling cutters **with irregular cutting edge spacing and an increased number of cutting edges**. Due to the **irregular cutting edge spacing** they achieve **very smooth running** and **long tool life**.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- **Significantly reduced vibration due to irregular cutting edge spacing**
- **Corrected thread profile for avoidance of profile distortions**
- **increased number of cutting edges.**
- **new coating for optimum wear resistance.**

Application:

For **UNF unified fine threads** ASME-B1.1.

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 139727 + 129100 HB**

Form **HE**: order with **No. 139727 + 129100 HE**

Spacing of the cutters: unequal spacing

Thread type: UNF

Thread type: UNF-LH

No. of teeth Z: 6

Threads per inch: 20

Nominal $\varnothing D_c$: 7.95 mm

Flute length L_c : 23.44 mm

Shank length L_s : 36 mm

Overall length L: 70 mm

Shank $\varnothing D_s$: 8 mm

Technical description

Threads per inch	20
Thread pitch	1.27 mm
No. of teeth Z	6
Thread Ø	11.11 mm
Shank Ø D _s	8 mm
Number of clamping slots	6
Full profile	yes
Thread type	UNF
Thread type	UNF-LH
Shank length L _s	36 mm
Overall length L	70 mm
Flute length L _c	23.44 mm
Feed f _z in steel < 750 N/mm ²	0.09
Thread size	7/16-20 UNF
Nominal Ø D _c	7.95 mm
Series	GARANT Master TM
Coating	TiAlN
Flank angle	60 degrees
Tool material	solid carbide
Shank	DIN 6535 HA with h6
Through-coolant	yes
Cutting direction	right-hand
Application for type of drilling	up to 2×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Shank tolerance	h6
Colour ring	green
Internal/external application	Internal

Type of product

thread milling cutter