

Garant
GARANT Master TM plain shank thread mill 2×D, TiAlN, UNF: 7/8-14

Order data

Order number	139727 7/8-14
GTIN	4062406058111
Item class	11D

Description
Version:

Solid carbide thread milling cutters **with irregular cutting edge spacing and an increased number of cutting edges**. Due to the **irregular cutting edge spacing** they achieve **very smooth running** and **long tool life**.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- **Significantly reduced vibration due to irregular cutting edge spacing**
- **Corrected thread profile for avoidance of profile distortions**
- **increased number of cutting edges.**
- **new coating for optimum wear resistance.**

Application:

For **UNF unified fine threads** ASME-B1.1.

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 139727 + 129100 HB**

Form **HE**: order with **No. 139727 + 129100 HE**

Spacing of the cutters: unequal spacing

Thread type: UNF

Thread type: UNF-LH

No. of teeth Z: 6

Threads per inch: 14

Nominal $\varnothing D_c$: 15.95 mm

Flute length L_c : 46.17 mm

Shank length L_s : 48 mm

Overall length L: 110 mm

Shank $\varnothing D_s$: 16 mm

Technical description

Overall length L	110 mm
No. of teeth Z	6
Shank length L _s	48 mm
Thread Ø	22.23 mm
Thread type	UNF
Thread type	UNF-LH
Threads per inch	14
Thread pitch	1.814 mm
Shank Ø D _s	16 mm
Number of clamping slots	6
Full profile	yes
Flute length L _c	46.17 mm
Feed f _z in steel < 750 N/mm ²	0.14
Thread size	7/8-14 UNF
Nominal Ø D _c	15.95 mm
Series	GARANT Master TM
Coating	TiAlN
Flank angle	60 degrees
Tool material	solid carbide
Shank	DIN 6535 HA with h6
Through-coolant	yes
Cutting direction	right-hand
Application for type of drilling	up to 2×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Shank tolerance	h6
Colour ring	green
Internal/external application	Internal

Type of product

thread milling cutter