



HOLEX Pro Steel High-precision countersink with unequal spacing 90°, TiAlN, External Ø Dc: 10,4 mm



Order data

Order number	150182 10,4
GTIN	4062406524241
Item class	12M

Description

Version:

All countersinks have 3 cutting edges, radially relieved.

Flutes are ground from solid.

HOLEX Pro Steel:

- Exact machining results in manual and machine use.
- Chatter-free running through extremely unequal spacing of the cutting edges for high-quality surfaces.
- Optimum tool life thanks to TiAlN high-performance coating.
- High process reliability due to optimised chip evacuation.
- Attractive cost/benefit ratio.

Application:

High precision countersinks for chatter-free countersinking.

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 2.5 mm

Overall length L: 50 mm

Shank Ø D_s: 6 mm

for countersunk screws DIN 7991: M5

Feed f in steel < 500 N/mm²: 0.12 mm/rev.

Technical description

Shank Ø D _s	6 mm
------------------------	------

Number of cutting edges Z	3
smallest countersink Ø for holes from	2.5 mm
External Ø	10.4 mm
Overall length L	50 mm
Feed f in steel < 500 N/mm ²	0.12 mm/rev.
for countersunk screws DIN 7991	M5
Shank tolerance	h9
Coating	TiAlN
Countersink tip angle	90 degrees
Tool material	HSS
Spacing of the countersink cutting edges	unequal spacing
Standard	DIN 335 C
Shank	Plain shank with h9
Through-coolant	no
Colour ring	green
Series	HOLEX Pro Steel
Type of product	Stepped drill and countersink