



HOLEX Pro Steel High-precision countersink with unequal spacing 90°, TiAlN, External Ø Dc: 6,3 mm



Order data

Order number	150182 6,3
GTIN	4062406523701
Item class	12M

Description

Version:

All countersinks have 3 cutting edges, radially relieved.

Flutes are ground from solid.

HOLEX Pro Steel:

- **Exact machining results in manual and machine use.**
- **Chatter-free running through extremely unequal spacing of the cutting edges for high-quality surfaces.**
- **Optimum tool life thanks to TiAlN high-performance coating.**
- **High process reliability due to optimised chip evacuation.**
- **Attractive cost/benefit ratio.**

Application:

High precision countersinks for chatter-free countersinking.

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 1.5 mm

Overall length L: 45 mm

Shank Ø D_s: 5 mm

for countersunk screws DIN 7991: M3

Feed f in steel < 500 N/mm²: 0.09 mm/rev.

Technical description

for countersunk screws DIN 7991	M3
---------------------------------	----

Number of cutting edges Z	3
Feed f in steel < 500 N/mm ²	0.09 mm/rev.
Shank tolerance	h9
External Ø	6.3 mm
Overall length L	45 mm
Shank Ø D _s	5 mm
smallest countersink Ø for holes from	1.5 mm
Coating	TiAlN
Countersink tip angle	90 degrees
Tool material	HSS
Spacing of the countersink cutting edges	unequal spacing
Standard	DIN 335 C
Shank	Plain shank with h9
Through-coolant	no
Colour ring	green
Series	HOLEX Pro Steel
Type of product	Stepped drill and countersink