

Garant

High-precision countersink with unequal spacing and 3 drive flats 90°, AlTiCN, External Ø Dc: 8 mm



Order data

Order number	150393 8
GTIN	4062406277147
Item class	11M

Description

Version:

All countersinks have 3 cutting edges, radially relieved.

Flutes are ground from solid.

High-precision countersink, produced with tight manufacturing tolerances similar to DIN 335-C.

Special geometry with **unequal spacing** and matching cutting edge preparation.

Newly developed AlTiCN coating especially **for stainless steels**.

Three **drive flats on the shank** for use in a 3-jaw chuck.

Application:

High-precision countersinks for chatter-free production of **precise, round 90° countersunk surfaces**.

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 2 mm

Overall length L: 50 mm

Shank Ø D_s: 6 mm

for countersunk screws ISO 2009, 2010, 7046, 7047: M4

Feed f in stainless steel < 900 N/mm²: 0.1 mm/rev.

Technical description

External Ø	8 mm
Feed f in stainless steel < 900 N/mm ²	0.1 mm/rev.

smallest countersink \varnothing for holes from	2 mm
Number of cutting edges Z	3
Overall length L	50 mm
Shank \varnothing D _s	6 mm
for countersunk screws ISO 2009, 2010, 7046, 7047	M4
Coating	AlTiCN
Countersink tip angle	90 degrees
Tool material	HSS E
Spacing of the countersink cutting edges	unequal spacing
Standard	DIN 335 C
Shank	Shank with h9 and three drive flats
Through-coolant	no
Colour ring	blue
Type of product	Stepped drill and countersink

Accessories

Countersink set No. 150393 with 3 drive flats, in a case 90° Number of countersinks 6	150394 6
Countersink set No. 150393 with 3 drive flats, in a case 90° Number of countersinks 7	150394 7