

Garant**Face reamer H7, uncoated, Nominal Ø DC: 10 mm****Order data**

Order number	162825 10
GTIN	4062406117276
Item class	110

Description**Version:**

Chuckling reamer cutting on the end face to achieve the most **accurate size possible**. The **optimised end face cutting** enables a **precise alignment fit** of the hole that is produced. Straight flute machine chucking reamers with **long flutes** for optimum chip evacuation.

Application:

For production of sequential holes with alignments that exactly match. For the highest demands for straightness of holes. For reaming of through holes and right to the bottom of blind holes.

Note:

No. 162830 Configurable reamers are available in the diameter range from 2.200 to 12.220 mm and for any choice of fit.

Application for type of drilling: for blind hole and through hole

Bore Ø tolerance: H7

Number of cutting edges Z: 6

Bore Ø tolerance: H7

Plunge cutting: 4.5 mm

Flute length L_c : 26 mm

Overhang L_1 : 84 mm

Overall length L: 133 mm

Number of cutting edges Z: 6

Technical description

Flute length L_c	26 mm
Nominal Ø D_c	10 mm
Bore Ø tolerance	H7
Shank Ø D_s	10 mm

Number of cutting edges Z	6
Overall length L	133 mm
Overhang L ₁	84 mm
Feed f in steel < 900 N/mm ²	0.2 mm/rev.
Plunge cutting	4.5 mm
recommended drill Ø in steel < 900 N/mm ²	9.8 mm
Coating	uncoated
Tool material	HSS E
Standard	Manufacturer's standard
Through-coolant	no
Shank	Parallel shank to e9
Application for type of drilling	for blind hole and through hole
Colour ring	green
Type of product	Reaming tool with non-detachable cutters