

NC reamer, uncoated, Nominal Ø DC: 3,64 mm



Order data

Order number	162902 3,64
GTIN	4062406138110
Item class	110

Description

Version:

Reamers such as 162900, but in 1/100 sizes.

Version suitable for NC similar to DIN 212 with straight shank Ø for standard chucking especially in hydraulic chucks or high precision collet chucks. For highest concentricity and process reliability. No need to order special collets.

With long flutes and left-hand helix.

Reamer manufacturing tolerances:

 $\leq \emptyset$ 5.50 mm: 0 / +0.004 mm > \emptyset 5.50 mm: 0 / +0.005 mm

Ordering example:

Desired dia. 6.24 mm – ordering particulars: article number 162902 6.24.

The 6.24 mm reamer with tolerance 0 / +0.005 mm is supplied.

Depending on availability, delivery time is from stock or max. 1 working week.

To determine which diameter you need for your desired fit, please see the following table (page 211). Often one reamer also covers further fits, since the tolerance bands overlap.

Note:

Reamers in whole number sizes and 1/10 sizes for H7 fit see No. 162900.

For reamers with diameters and fits to specification see No. 162951.

You can find the associated table of fits in Catalogue 51 on page 199.

Application for type of drilling: for through holes

Bore \varnothing tolerance: 0 / 0.004 Number of cutting edges Z: 6 Bore \varnothing tolerance: 0 / 0.004 Flute length L_c: 18 mm Overhang L₁: 42 mm Overall length L: 70 mm Number of cutting edges Z: 6

Shank Ø D_s: 4 mm

Technical description

2.4
3.64 mm
42 mm
0.2 mm/rev.
0 / 0.004
18 mm
4 mm
70 mm
6
uncoated
HSS E
Manufacturer's standard
no
DIN 1835 A to h6
for through holes
green
Reaming tool with non- detachable cutters