## Garant

#### NC reamer, uncoated, Nominal Ø DC: 9,93 mm



## **Order data**

Order number	162902 9,93
GTIN	4062406144500
Item class	110

## Description

#### Version:

#### Reamers such as 162900, but in 1/100 sizes.

**Version suitable for NC** similar to DIN 212 with straight shank Ø for standard chucking especially in hydraulic chucks or high precision collet chucks. For highest concentricity and process reliability. No need to order special collets.

With long flutes and left-hand helix.

#### Reamer manufacturing tolerances:

 $\leq \emptyset$  5.50 mm: 0 / +0.004 mm

> Ø 5.50 mm: 0 / +0.005 mm

#### **Ordering example:**

Desired dia. 6.24 mm – ordering particulars: article number 162902 6.24.

The 6.24 mm reamer with tolerance 0 / +0.005 mm is supplied.

Depending on availability, delivery time is from stock or max. 1 working week.

To determine which diameter you need for your desired fit, please see the following table (page

211). Often one reamer also covers further fits, since the tolerance bands overlap.

#### Note:

Reamers in whole number sizes and 1/10 sizes for H7 fit see No. 162900.

For reamers with diameters and fits to specification see No. 162951.

You can find the associated table of fits in Catalogue 51 on page 199.

Application for type of drilling: for through holes

Bore Ø tolerance: 0 / 0,005

Number of cutting edges Z: 6

Bore Ø tolerance: 0 / 0,005

Flute length L<sub>c</sub>: 38 mm

Overhang L<sub>1</sub>: 92 mm

Overall length L: 133 mm

Number of cutting edges Z: 6

Shank Ø D<sub>s</sub>: 10 mm

# **Technical description**

Shank $Ø D_s$	10 mm
Flute length L <sub>c</sub>	38 mm
Feed f in steel < 750 N/mm <sup>2</sup>	0.25 mm/rev.
Overall length L	133 mm
Bore Ø tolerance	0 / 0,005
Overhang L <sub>1</sub>	92 mm
Number of cutting edges Z	б
Nominal Ø D <sub>c</sub>	9.93 mm
Coating	uncoated
Tool material	HSS E
Standard	Manufacturer's standard
Through-coolant	no
Shank	DIN 1835 A to h6
Application for type of drilling	for through holes
Colour ring	green
Type of product	Reaming tool with non- detachable cutters