

**Garant**
**Machine reamer H7, uncoated, Nominal  $\varnothing$  DC: 1,8 mm**

**Order data**

Order number	163000 1,8
GTIN	4045197252579
Item class	110

**Description**
**Version:**

With long flutes and left-hand helix.  
 From size 1.8 even number of teeth and uneven spacing.  
 Up to size 3.7 both ends with external centres;  
 from size 3.9 both ends with internal centres.

**Reamers finish ground for fit H7.**
**Application:**

For reaming through holes. Also suitable for blind holes (from 3.9 mm  $\varnothing$ ) due to short chamfer lead.

**Note:**

- **Straight flute machine chucking reamers – available ex-stock.**
- **For reamers with other diameters and fits see No. 162951.**

Application for type of drilling: for through holes

Bore  $\varnothing$  tolerance: H7

Number of cutting edges Z: 4

Bore  $\varnothing$  tolerance: H7

Flute length  $L_c$ : 10 mm

Overhang  $L_1$ : 20 mm

Overall length L: 46 mm

Number of cutting edges Z: 4

Shank  $\varnothing$   $D_s$ : 1.8 mm

**Technical description**

Overhang $L_1$	20 mm
Nominal $\varnothing$ $D_c$	1.8 mm
Feed f in steel < 750 N/mm <sup>2</sup>	0.15 mm/rev.

Shank tolerance	h9
Shank $\varnothing D_s$	1.8 mm
Overall length L	46 mm
Flute length $L_c$	10 mm
Number of cutting edges Z	4
recommended drill $\varnothing$ in steel < 750 N/mm <sup>2</sup>	1.7 mm
Bore $\varnothing$ tolerance	H7
Coating	uncoated
Tool material	HSS E
Standard	DIN 212 B
Through-coolant	no
Shank	Plain shank with h9
Application for type of drilling	for through holes
Colour ring	without
Type of product	Reaming tool with non-detachable cutters