

Garant

Solid carbide side milling cutter HPC, TiAlN, $\varnothing \times \text{width} \pm 0.1 \times k11$: 40X10 mm


Order data

Order number	185015 40X10
GTIN	4062406397364
Item class	11V

Description
Version:

Precision solid carbide side milling cutters in the HPC machining range. **With new high-performance coating** for very long tool life.

Use as a set: Cutters with the same $\varnothing$ and same number of teeth can be combined as a set and adjusted to the required width. Since the cutters have no raised bore collar, the staggered teeth mesh with each other.

2-piece sets are particularly economical. By reversing the side milling cutters, both side edges of each cutter can be used.

Note:

- **Do not clamp the cutters in a set without a sufficiently thick arbor spacer ring, otherwise the cutters will be damaged.**
- **See Product Group 30 for suitable arbor spacer rings.**
- **Slots milled from solid: f_z for $a_e = 0.1 \times D$.**

Successor product to No. 185010.

Bore $\varnothing$ H6 d_1 : 13 mm

No. of teeth Z: 12

Collar thickness $b \pm 0.1$: 7.2 mm

Collar $\varnothing$ $d_2 \pm 1$: 28 mm

Tooth height Z_h : 6 mm

Capability of combining 2 cutters of the same width A/B: 10 mm

Technical description

Cutting width	10 mm
Cutting edge $\varnothing D_c$	40 mm
Capability of combining 2 cutters of the same width A/B	10 mm
Collar thickness $b \pm 0.1$	7.2 mm
Capability of combining 2 cutters of the same width, results in overall width E	18.5 - 19.8 mm
Shank type	with bore
Feed f_z in steel $< 900 \text{ N/mm}^2$	0.03 mm
Tooth height Z_h	6 mm
No. of teeth Z	12
Collar $\varnothing d_2 \pm 1$	28 mm
Bore $\varnothing H6 d_1$	13 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 885 A
Type	N
Tolerance nominal $\varnothing$	± 0.1
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Machining strategy	HPC
Through-coolant	no
Colour ring	without
Type of product	Side milling cutter