

Garant

Solid carbide side milling cutter HPC, TiAlN, $\varnothing \times \text{width} \pm 0.1 \times k11$: 80X14 mm



Order data

Order number	185015 80X14
GTIN	4062406397555
Item class	11V

Description

Version:

Precision solid carbide side milling cutters in the HPC machining range. **With new high-performance coating** for very long tool life.

Use as a set: Cutters with the same \varnothing and same number of teeth can be combined as a set and adjusted to the required width. Since the cutters have no raised bore collar, the staggered teeth mesh with each other.

2-piece sets are particularly economical. By reversing the side milling cutters, both side edges of each cutter can be used.

Note:

- **Do not clamp the cutters in a set without a sufficiently thick arbor spacer ring, otherwise the cutters will be damaged.**
- **See Product Group 30 for suitable arbor spacer rings.**
- **Slots milled from solid: f_z for $a_e = 0.1 \times D$.**

Successor product to No. 185010.

Bore \varnothing H6 d_1 : 27 mm

No. of teeth Z: 14

Collar thickness $b \pm 0.1$: 8.5 mm

Collar \varnothing $d_2 \pm 1$: 50 mm

Tooth height Z_h : 15 mm

Capability of combining 2 cutters of the same width A/B: 14 mm

Technical description

Bore \varnothing H6 d ₁	27 mm
Tooth height Zh	15 mm
Collar \varnothing d ₂ ±1	50 mm
Cutting edge \varnothing D _c	80 mm
Cutting width	14 mm
No. of teeth Z	14
Capability of combining 2 cutters of the same width A/B	14 mm
Shank type	with bore
Capability of combining 2 cutters of the same width, results in overall width E	25 - 27.8 mm
Collar thickness b ±0.1	8.5 mm
Feed f _z in steel < 900 N/mm ²	0.06 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 885 A
Type	N
Tolerance nominal \varnothing	± 0.1
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Machining strategy	HPC
Through-coolant	no
Colour ring	without
Type of product	Side milling cutter