

Solid carbide side milling cutter HPC, TiAIN, Ø×width ± 0.1×k11: 80X4 mm



Order data

Order number	185015 80X4
GTIN	4062406397500
Item class	11V

Description

Version:

Precision solid carbide side milling cutters in the HPC machining range. **With new high-performance coating** for very long tool life.

Use as a set: Cutters with the same \emptyset and same number of teeth can be combined as a set and adjusted to the required width. Since the cutters have no raised bore collar, the staggered teeth mesh with each other.

2-piece sets are particularly economical. By reversing the side milling cutters, both side edges of each cutter can be used.

Note:

- Do not clamp the cutters in a set without a sufficiently thick arbor spacer ring, otherwise the cutters will be damaged.
- See Product Group 30 for suitable arbor spacer rings.
- · Slots milled from solid: f_z for $a_e = 0.1 \times D$.

Successor product to No. 185010.

Bore \varnothing H6 d₁: 27 mm No. of teeth Z: 22

Collar thickness b ±0.1: 2.3 mm

Collar \emptyset d₂ ±1: 50 mm Tooth height Zh: 15 mm Capability of combining 2 cutters of the same width A/B: 4 mm

Technical description

Cutting edge \emptyset D _c	80 mm
Capability of combining 2 cutters of different width, results in overall width E	8.1 - 8.8 mm
No. of teeth Z	22
Bore Ø H6 d₁	27 mm
Tooth height Zh	15 mm
Collar thickness b ±0.1	2.3 mm
Capability of combining 2 cutters of different width A	4 mm
Capability of combining 2 cutters of the same width, results in overall width E	7.3 - 7.8 mm
Capability of combining 2 cutters of the same width A/B	4 mm
Cutting width	4 mm
Feed f_z in steel < 900 N/mm ²	0.045 mm
Collar \emptyset d ₂ ±1	50 mm
Shank type	with bore
Capability of combining 2 cutters of different width B	5 mm
Coating	TiAIN
Tool material	Solid carbide
Standard	DIN 885 A
Туре	N
Tolerance nominal Ø	± 0.1
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Machining strategy	HPC
Through-coolant	no
Colour ring	without
Type of product	Side milling cutter

