

Garant
GARANT Master Alu solid carbide milling cutter HPC, uncoated, Ø f8 DC / RS1: 2L mm

Order data

Order number	201070 2L
GTIN	4062406184995
Item class	11Z

Description
Version:

Precision balanced tools, ideally suited for use on **high-speed spindles**. Special geometry for optimum chip evacuation thanks to **newly developed balancing process**.

Very smooth cutting action for **outstanding surface quality**.

Tolerance nominal Ø: e8

No. of teeth Z: 1

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: Plain shank

Balance quality with shank: G 1.8 with HA

No. of teeth Z: 1

Flute length L_c : 11 mm

Overall length L: 50 mm

Shank Ø D_s : 6 mm

Feed f_z for slot milling in short-chipping aluminium: 0.02 mm

Feed f_z for side milling in short-chipping aluminium: 0.04 mm

Technical description

Shank Ø D_s	6 mm
Overall length L	50 mm
Shank	Plain shank
No. of teeth Z	1

Tolerance nominal Ø	e8
Helix angle	30 degrees
Balance quality with shank	G 1.8 with HA
Feed f_z for side milling in short-chipping aluminium	0.04 mm
Cutting edge Ø D_c	2 mm
Flute length L_c	11 mm
Direction of infeed	horizontal, oblique and vertical
Feed f_z for slot milling in short-chipping aluminium	0.02 mm
Corner chamfer angle	90 degrees
Series	GARANT Master Alu
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------