

Garant
GARANT Master Alu solid carbide milling cutter HPC, DLC, Ø e8 DC: 6L mm

Order data

Order number	201075 6L
GTIN	4062406186531
Item class	11Z

Description
Version:

Precision balanced tools, ideally suited for use on **high-speed spindles**. Special geometry for optimum chip evacuation thanks to **newly developed balancing process**.

Very smooth cutting action for **outstanding surface quality**.

Tolerance nominal \varnothing : e8

No. of teeth Z: 1

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: Plain shank

Balance quality with shank: G 1.8 with HA

No. of teeth Z: 1

Flute length L_c : 16 mm

Overhang length L_1 incl. recess: 24 mm

Recess $\varnothing D_1$: 5.5 mm

Overall length L: 50 mm

Shank $\varnothing D_s$: 6 mm

Technical description

Recess $\varnothing D_1$	5.5 mm
Cutting edge $\varnothing D_c$	6 mm
Shank	Plain shank
Feed f_z for side milling in short-chipping aluminium	0.08 mm
Flute length L_c	16 mm

Tolerance nominal \varnothing	e8
Balance quality with shank	G 1.8 with HA
Shank $\varnothing D_s$	6 mm
Direction of infeed	horizontal, oblique and vertical
Overhang length L_1 incl. recess	24 mm
Helix angle	30 degrees
No. of teeth Z	1
Feed f_z for slot milling in short-chipping aluminium	0.06 mm
Overall length L	50 mm
Corner chamfer angle	90 degrees
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------