

Garant
Solid carbide micro slot drill, DLC, Ø DC × L1: 1,2X6 mm

Order data

| | |
|--------------|---------------|
| Order number | 201140 1,2X6 |
| GTIN | 4045197912978 |
| Item class | 11X |

Description
Version:

With **advanced DLC sp² coating**. For the **highest demands regarding performance and precision in aluminium materials**. **Extremely tight tolerances** ensure maximum accuracy. Double relief ground with 2 hollow-ground chamfers. **Recess angle $\alpha = 16^\circ$** .

Tolerances:

· **Neck Ø: $D_1 = 0 / -0.01$ mm.**

Note:

At greater tool overhang lengths, use a reduced value for a_p !
 Values for:
 slots milled from solid: $a_p = 0.25 \times D \times a_{p,corr}$
 side milling: $a_p = 0.5 \times D \times a_{p,corr}$
To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)!
 e.g: $vf = 18000 \text{ [rpm]} \times fz \text{ [mm/Z]} \times z$

Through-coolant: no

Tolerance nominal Ø: $0 / -0.005$

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h5

No. of teeth Z: 2

Flute length L_c : 1.8 mm

Overhang length L_1 incl. recess: 6 mm

Recess Ø D_1 : 1.14 mm

Overall length L: 45 mm

Shank Ø D_s : 4 mm

Technical description

| | |
|-----------------------------------------------|----------|
| Feed f_z for slot milling in cast aluminium | 0.025 mm |
|-----------------------------------------------|----------|

| | |
|-----------------------------------------------|----------------------------------|
| Recess $\varnothing D_1$ | 1.14 mm |
| Feed f_z for side milling in cast aluminium | 0.03 mm |
| Tolerance nominal \varnothing | 0 / -0.005 |
| No. of teeth Z | 2 |
| Overhang length L_1 incl. recess | 6 mm |
| Overall length L | 45 mm |
| Direction of infeed | horizontal, oblique and vertical |
| Shank $\varnothing D_s$ | 4 mm |
| Flute length L_c | 1.8 mm |
| Shank | DIN 6535 HA to h5 |
| Cutting edge $\varnothing D_c$ | 1.2 mm |
| Helix angle | 30 degrees |
| Correction factor $a_{p,corr}$ | 1 |
| Corner chamfer angle | 90 degrees |
| Coating | DLC |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Type | W |
| Cutting width a_e for milling operation | 0.5×D for side milling |
| Cutting width a_e for milling operation | Full slot cutting depth 1×D |
| Through-coolant | no |
| Colour ring | yellow |
| Type of product | End mill |