

# Solid carbide micro slot drill, DLC, Ø Dc×L1: 1X10 mm



# **Order data**

Order number	201141 1X10
GTIN	4062406387266
Item class	11X

### **Description**

#### **Version:**

With advanced DLC sp<sup>2</sup> coating. For the highest demands regarding performance and precision in aluminium materials. Extremely tight tolerances ensure maximum accuracy. Double relief ground with 2 hollow-ground chamfers. Recess angle  $\alpha = 16^{\circ}$ . Tolerances:

• Neck Ø:  $D_1 = 0 / -0.01 \text{ mm}$ .

Extra-sturdy shank to reduce the tendency to vibrate.

#### Note:

At greater tool overhang lengths, use a reduced value for  $a_p!$ <br/> br> Values for:<br/> br> slots milled from solid:  $a_p = 0.25 \times D \times a_{p \text{ corr}} < br>$  side milling:  $a_p = 0.5 \times D \times a_{p \text{ corr}} < br>$  To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)!<br/> br> e.g: br> vf = 18000 [rpm]× fz [mm/Z]× z

Through-coolant: no

Tolerance nominal  $\emptyset$ : 0 / -0.005

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h5

No. of teeth Z: 2

Flute length L<sub>c</sub>: 1.5 mm

Overhang length L<sub>1</sub> incl. recess: 10 mm

Recess  $\emptyset$  D<sub>1</sub>: 0.95 mm Overall length L: 55 mm Shank  $\emptyset$  D<sub>4</sub>: 6 mm

# **Technical description**

Shank Ø D <sub>s</sub>	6 mm
Feed f <sub>z</sub> for slot milling in cast aluminium	0.025 mm
Corner chamfer angle	90 degrees
No. of teeth Z	2
Helix angle	30 degrees
Correction factor a <sub>p corr</sub>	0.5
Recess Ø D <sub>1</sub>	0.95 mm
Overall length L	55 mm
Tolerance nominal Ø	0 / -0.005
Shank	DIN 6535 HA to h5
Direction of infeed	horizontal, oblique and vertical
Overhang length L <sub>1</sub> incl. recess	10 mm
Flute length L <sub>c</sub>	1.5 mm
Cutting edge $\emptyset$ $D_{c}$	1 mm
Feed f <sub>z</sub> for side milling in cast aluminium	0.03 mm
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Туре	W
Cutting width a <sub>e</sub> for milling operation	Full slot cutting depth 1×D
Cutting width a <sub>e</sub> for milling operation	0.5×D for side milling
Through-coolant	no
Colour ring	yellow
Type of product	End mill