

Solid carbide micro slot drill, DLC, Ø Dc×L1: 2X25 mm



Order data

Order number	201141 2X25
GTIN	4062406387464
Item class	11X

Description

Version:

With advanced DLC sp² coating. For the highest demands regarding performance and precision in aluminium materials. Extremely tight tolerances ensure maximum accuracy. Double relief ground with 2 hollow-ground chamfers. Recess angle $\alpha = 16^{\circ}$. Tolerances:

• Neck Ø: $D_1 = 0 / -0.01 \text{ mm}$.

Extra-sturdy shank to reduce the tendency to vibrate.

Note:

At greater tool overhang lengths, use a reduced value for $a_p!$
 br> Values for:
 br> slots milled from solid: $a_p = 0.25 \times D \times a_{p \text{ corr}} < br>$ side milling: $a_p = 0.5 \times D \times a_{p \text{ corr}} < br>$ To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)!
 br> e.g: br> vf = 18000 [rpm]× fz [mm/Z]× z

Through-coolant: no

Tolerance nominal \emptyset : 0 / -0.005

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h5

No. of teeth Z: 2 Flute length L_c: 3 mm

Overhang length L₁ incl. recess: 25 mm

Recess \emptyset D₁: 1.91 mm Overall length L: 65 mm Shank \emptyset D₄: 6 mm

Technical description

Helix angle	30 degrees
Flute length L _c	3 mm
Overhang length L ₁ incl. recess	25 mm
Tolerance nominal Ø	0 / -0.005
Feed f _z for slot milling in cast aluminium	0.03 mm
Corner chamfer angle	90 degrees
No. of teeth Z	2
Shank	DIN 6535 HA to h5
Direction of infeed	horizontal, oblique and vertical
Overall length L	65 mm
Cutting edge Ø D _c	2 mm
Feed f _z for side milling in cast aluminium	0.033 mm
Correction factor a _{p corr}	0.35
Recess Ø D ₁	1.91 mm
Shank Ø D _s	6 mm
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Туре	W
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Cutting width a _e for milling operation	0.5×D for side milling
Through-coolant	no
Colour ring	yellow
Type of product	End mill