

Garant
Solid carbide slot drill, AlCrN, Ø e8 DC: 7,75 mm

Order data

Order number	201302 7,75
GTIN	4045197862426
Item class	11X

Description
Version:

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 2

Flute length L_c : 12 mm

Overall length L: 58 mm

Shank Ø D_s : 8 mm

Shank form: HB

Corner chamfer width at 45°: 0.2 mm

Technical description

Feed f_z for slot milling in steel < 750 N/mm ²	0.04 mm
No. of teeth Z	2
Corner chamfer width at 45°	0.2 mm
Tolerance nominal Ø	e8
Direction of infeed	horizontal, oblique and vertical
Overall length L	58 mm

Flute length L_c	12 mm
Cutting edge $\varnothing D_c$	7.75 mm
Shank form	HB
Feed f_z for side milling in steel $< 750 \text{ N/mm}^2$	0.05 mm
Shank	DIN 6535 HB to h6
Shank $\varnothing D_s$	8 mm
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Colour ring	without
Type of product	End mill