

Garant
Solid carbide milling cutter, AlCrN, Ø e8 DC: 15,7 mm

Order data

Order number	201306 15,7
GTIN	4045197863010
Item class	11X

Description
Version:

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 2

Flute length L_c : 32 mm

Overhang length L_1 incl. recess: 44 mm

Recess Ø D_1 : 15.4 mm

Overall length L: 92 mm

Shank Ø D_s : 16 mm

Technical description

No. of teeth Z	2
Feed f_z for side milling in steel < 750 N/mm ²	0.13 mm
Cutting edge Ø D_c	15.7 mm
Feed f_z for slot milling in steel < 750 N/mm ²	0.08 mm
Tolerance nominal Ø	e8
Recess Ø D_1	15.4 mm

Shank form	HB
Overall length L	92 mm
Flute length L_c	32 mm
Direction of infeed	horizontal, oblique and vertical
Overhang length L_1 incl. recess	44 mm
Shank	DIN 6535 HB to h6
Shank $\varnothing D_s$	16 mm
Helix angle	30 degrees
Corner chamfer angle	90 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Colour ring	without
Type of product	End mill