


Garant
Solid carbide milling cutter, AlCrN, Ø e8 DC: 7,75 mm

Order data

Order number	201306 7,75
GTIN	4045197862914
Item class	11X

Description
Version:

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 2

Flute length L_c : 19 mm

Overhang length L_1 incl. recess: 27 mm

Recess Ø D_1 : 7.55 mm

Overall length L: 63 mm

Shank Ø D_s : 8 mm

Technical description

Flute length L_c	19 mm
Tolerance nominal Ø	e8
Direction of infeed	horizontal, oblique and vertical
Recess Ø D_1	7.55 mm
Shank Ø D_s	8 mm
Shank form	HB

Feed f_z for slot milling in steel < 750 N/mm ²	0.04 mm
Overhang length L_1 incl. recess	27 mm
Feed f_z for side milling in steel < 750 N/mm ²	0.05 mm
Cutting edge $\varnothing D_c$	7.75 mm
No. of teeth Z	2
Overall length L	63 mm
Shank	DIN 6535 HB to h6
Helix angle	30 degrees
Corner chamfer angle	90 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill