


Garant
Solid carbide milling cutter, AlCrN, Ø e8 DC: 13,7 mm

Order data

Order number	201307 13,7
GTIN	4045197930231
Item class	11X

Description
Version:

Improved coating for general-purpose applications in steel and cast iron.

Dimensions similar to **DIN 6527**.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HE to h6

No. of teeth Z: 2

Flute length L_c : 26 mm

Overhang length L_1 incl. recess: 38 mm

Recess Ø D_1 : 13.5 mm

Overall length L: 83 mm

Shank Ø D_s : 14 mm

Technical description

Corner chamfer width at 45°	0.1 mm
Cutting edge Ø D_c	13.7 mm
No. of teeth Z	2
Direction of infeed	horizontal, oblique and vertical
Tolerance nominal Ø	e8
Feed f_z for slot milling in steel < 750 N/mm ²	0.07 mm

Shank form	HB
Shank	DIN 6535 HE to h6
Overall length L	83 mm
Feed f_z for side milling in steel < 750 N/mm ²	0.1 mm
Helix angle	30 degrees
Overhang length L_1 incl. recess	38 mm
Recess $\varnothing D_1$	13.5 mm
Flute length L_c	26 mm
Shank $\varnothing D_s$	14 mm
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Through-coolant	no
Colour ring	without
Type of product	End mill