

**Garant**
**Solid carbide milling cutter, AlCrN, Ø e8 DC: 0,7 mm**

**Order data**

Order number	201308 0,7
GTIN	4045197863102
Item class	11X

**Description**
**Version:**

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

**Note:**

**Successor product for No. 201630 and 201522.**

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 2

Flute length  $L_c$ : 2 mm

Overall length L: 38 mm

Shank Ø  $D_s$ : 3 mm

Shank form: HA

Feed  $f_z$  for slot milling in steel < 750 N/mm<sup>2</sup>: 0.003 mm

**Technical description**

Direction of infeed	horizontal, oblique and vertical
Feed $f_z$ for side milling in steel < 750 N/mm <sup>2</sup>	0.003 mm
No. of teeth Z	2
Tolerance nominal Ø	e8
Shank Ø $D_s$	3 mm

Cutting edge $\varnothing D_c$	0.7 mm
Feed $f_z$ for slot milling in steel $< 750 \text{ N/mm}^2$	0.003 mm
Shank	DIN 6535 HA to h6
Flute length $L_c$	2 mm
Overall length $L$	38 mm
Shank form	HA
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width $a_e$ for milling operation	$0.3 \times D$ for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Colour ring	without
Type of product	End mill