

Garant
Solid carbide milling cutter, AlCrN, Ø e8 DC: 0,9 mm

Order data

Order number	201308 0,9
GTIN	4045197863126
Item class	11X

Description
Version:

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

Note:

Successor product for No. 201630 and 201522.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 2

Flute length L_c : 2.5 mm

Overall length L: 38 mm

Shank Ø D_s : 3 mm

Shank form: HA

Feed f_z for slot milling in steel < 750 N/mm²: 0.003 mm

Technical description

Shank	DIN 6535 HA to h6
Shank Ø D_s	3 mm
Overall length L	38 mm
Feed f_z for side milling in steel < 750 N/mm ²	0.003 mm
Feed f_z for slot milling in steel < 750 N/mm ²	0.003 mm

Tolerance nominal \varnothing	e8
Flute length L_c	2.5 mm
Direction of infeed	horizontal, oblique and vertical
No. of teeth Z	2
Shank form	HA
Cutting edge $\varnothing D_c$	0.9 mm
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	0.3xD for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1xD
Through-coolant	no
Colour ring	without
Type of product	End mill