

**Garant**
**Solid carbide milling cutter, AlCrN, Ø e8 DC: 12 mm**

**Order data**

Order number	201308 12
GTIN	4045197863409
Item class	11X

**Description**
**Version:**

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

**Note:**

**Successor product for No. 201630 and 201522.**

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 2

Flute length  $L_c$ : 26 mm

Overhang length  $L_1$  incl. recess: 38 mm

Recess Ø  $D_1$ : 11.8 mm

Overall length L: 83 mm

Shank Ø  $D_s$ : 12 mm

**Technical description**

No. of teeth Z	2
Direction of infeed	horizontal, oblique and vertical
Shank Ø $D_s$	12 mm
Feed $f_z$ for slot milling in steel < 750 N/mm <sup>2</sup>	0.07 mm
Overall length L	83 mm

Recess $\varnothing D_1$	11.8 mm
Flute length $L_c$	26 mm
Overhang length $L_1$ incl. recess	38 mm
Feed $f_z$ for side milling in steel $< 750 \text{ N/mm}^2$	0.1 mm
Tolerance nominal $\varnothing$	e8
Shank form	HB
Corner chamfer width at $45^\circ$	0.3 mm
Cutting edge $\varnothing D_c$	12 mm
Shank	DIN 6535 HB to h6
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width $a_e$ for milling operation	$0.3 \times D$ for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Colour ring	without
Type of product	End mill

## Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank  $\varnothing$  tool 12 mm

SZ2025 12