


Garant
Solid carbide milling cutter, AlCrN, Ø e8 DC: 16 mm

Order data

Order number	201308 16
GTIN	4045197863447
Item class	11X

Description
Version:

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

Note:

Successor product for No. 201630 and 201522.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 2

Flute length L_c : 32 mm

Overhang length L_1 incl. recess: 44 mm

Recess Ø D_1 : 15.7 mm

Overall length L: 92 mm

Shank Ø D_s : 16 mm

Technical description

No. of teeth Z	2
Shank	DIN 6535 HB to h6
Recess Ø D_1	15.7 mm
Overhang length L_1 incl. recess	44 mm
Cutting edge Ø D_c	16 mm

Corner chamfer width at 45°	0.4 mm
Direction of infeed	horizontal, oblique and vertical
Shank form	HB
Feed f_z for slot milling in steel < 750 N/mm ²	0.08 mm
Tolerance nominal \varnothing	e8
Flute length L_c	32 mm
Overall length L	92 mm
Shank $\varnothing D_s$	16 mm
Feed f_z for side milling in steel < 750 N/mm ²	0.13 mm
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm

SZ2025 16