

**Garant**
**Solid carbide milling cutter, AlCrN, Ø e8 DC: 18 mm**

**Order data**

Order number	201308 18
GTIN	4045197863454
Item class	11X

**Description**
**Version:**

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

**Note:**

**Successor product for No. 201630 and 201522.**

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 2

Flute length  $L_c$ : 32 mm

Overhang length  $L_1$  incl. recess: 44 mm

Recess Ø  $D_1$ : 17.7 mm

Overall length L: 92 mm

Shank Ø  $D_s$ : 18 mm

**Technical description**

Recess Ø $D_1$	17.7 mm
Shank	DIN 6535 HB to h6
Feed $f_z$ for side milling in steel < 750 N/mm <sup>2</sup>	0.15 mm
Direction of infeed	horizontal, oblique and vertical
Shank Ø $D_s$	18 mm

Overhang length $L_1$ incl. recess	44 mm
Shank form	HB
Overall length L	92 mm
Cutting edge $\varnothing D_c$	18 mm
Tolerance nominal $\varnothing$	e8
Feed $f_z$ for slot milling in steel < 750 N/mm <sup>2</sup>	0.09 mm
Flute length $L_c$	32 mm
Corner chamfer width at 45°	0.4 mm
No. of teeth Z	2
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width $a_e$ for milling operation	0.3×D for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill