


Solid carbide milling cutter, uncoated, Ø e8 DC: 7 mm

Order data

Order number	2013107
GTIN	4045197863515
Item class	12X

Description
Version:

Dimensions similar to **DIN 6527**.

Note:

Successor product for No. 201640 and 201405.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 2

Flute length L_c : 16 mm

Overall length L: 63 mm

Shank Ø D_s : 8 mm

Shank form: HB

Corner chamfer width at 45°: 0.2 mm

Technical description

Flute length L_c	16 mm
Tolerance nominal Ø	e8
Feed f_z for side milling in steel < 750 N/mm ²	0.05 mm
Feed f_z for slot milling in steel < 750 N/mm ²	0.04 mm
Shank Ø D_s	8 mm

Cutting edge $\varnothing D_c$	7 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Overall length L	63 mm
Shank form	HB
Corner chamfer width at 45°	0.2 mm
No. of teeth Z	2
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill