

Garant
GARANT Master INOX solid carbide slot drill HPC, TiAlN, Ø e8 DC: 5 mm

Order data

Order number	201647 5
GTIN	4062406112981
Item class	11X

Description
Version:

Double relief ground **2 chamfers hollow ground** for use in **HPC applications**.

Greater oxidation resistance and high-temperature hardness.

Can be used at high cutting speeds, particularly suitable even for Toolox®.

Note:

Successor product to No. 201644.

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 50 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 2

Flute length L_c : 13 mm

Overhang length L_1 incl. recess: 21 mm

Recess Ø D_1 : 4.8 mm

Overall length L: 57 mm

Shank Ø D_s : 6 mm

Technical description

No. of teeth Z	2
Overall length L	57 mm
Tolerance nominal Ø	e8
Feed f_z for side milling in INOX < 900 N/mm ²	0.022 mm

Flute length L_c	13 mm
Direction of infeed	horizontal, oblique and vertical
Recess $\varnothing D_1$	4.8 mm
Shank	DIN 6535 HA to h6
Shank $\varnothing D_s$	6 mm
Corner chamfer width at 45°	0.08 mm
Feed f_z for slot milling in stainless steel < 900 N/mm ²	0.018 mm
Overhang length L_1 incl. recess	21 mm
Helix angle	50 degrees
Cutting edge $\varnothing D_c$	5 mm
Corner chamfer angle	45 degrees
Series	GARANT Master INOX
Coating	TiAlN
Tool material	solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	Full slot cutting depth 1xD
Cutting width a_e for milling operation	Full slot cutting depth 1xD
Through-coolant	no
Machining strategy	HPC
Colour ring	blue
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------