

Garant
GARANT Master Alu PickPocket solid carbide roughing end mill HPC, DLC, Ø e8 DC: 4M mm

Order data

Order number	202004 4M
GTIN	4062406380908
Item class	11X

Description
Version:

With the latest generation of DLC coating sp^2 .

For roughing and finishing.

Up to $2 \times D$ into solid material at very high feed rates and smooth cutting action.

Very high feed rates when plunging vertically.

Ramping capability up to 45° .

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 11 mm

Overhang length L_1 incl. recess: 17 mm

Recess Ø D_1 : 3.7 mm

Overall length L: 57 mm

Shank Ø D_s : 6 mm

Technical description

Cutting edge Ø D_c	4 mm
No. of teeth Z	3

Shank	DIN 6535 HA to h6
Feed f_z for slot milling in short-chipping aluminium	0.05 mm
Direction of infeed	horizontal, oblique and vertical
Tolerance nominal \varnothing	e8
Balance quality with shank	G 2.5 with HA
Helix angle	42 degrees
Shank $\varnothing D_s$	6 mm
Overall length L	57 mm
Feed f_z for side milling in short-chipping aluminium	0.06 mm
Corner rounding r_v	0.1 mm
Flute length L_c	11 mm
Recess $\varnothing D_1$	3.7 mm
Overhang length L_1 incl. recess	17 mm
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill