

Garant

GARANT Master Alu PickPocket solid carbide roughing end mill with through-coolant HPC, DLC, Ø e8 DC: 12 mm



Order data

Order number	202006 12
GTIN	4062406126193
Item class	11X

Description

Version:

For roughing and finishing.

Up to $2 \times D$ into solid material at very high feed rates and smooth cutting action.

Very high feed rates when plunging vertically.

Ramping capability up to 45° .

Improved chip evacuation due to central through-coolant. Due to the patented geometry also suitable for boring.

With the latest generation of DLC coating sp^2 .

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Tolerance nominal \varnothing : e8

No. of teeth Z: 3

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 26 mm

Overhang length L_1 incl. recess: 36 mm

Recess $\varnothing D_1$: 11.8 mm

Overall length L: 83 mm

Shank $\varnothing D_s$: 12 mm

Technical description

Balance quality with shank	G 2.5 with HA
Shank $\varnothing D_s$	12 mm
Shank	DIN 6535 HA to h6
No. of teeth Z	3
Overhang length L_1 incl. recess	36 mm
Tolerance nominal \varnothing	e8
Helix angle	42 degrees
Cutting edge $\varnothing D_c$	12 mm
Flute length L_c	26 mm
Feed f_z for side milling in short-chipping aluminium	0.15 mm
Direction of infeed	horizontal, oblique and vertical
Recess $\varnothing D_1$	11.8 mm
Overall length L	83 mm
Feed f_z for slot milling in short-chipping aluminium	0.1 mm
Corner rounding r_v	0.32 mm
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	yes
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB

129100 HB