# Garant

GARANT Master Alu PickPocket solid carbide roughing end mill with throughcoolant HPC, DLC, Ø e8 DC: 9 mm



### Order data

Order number	202006 9
GTIN	4062406126155
Item class	11X

### Description

#### Version:

For roughing and finishing. Up to  $2 \times D$  into solid material at very high feed rates and smooth cutting action. Very high feed rates when plunging vertically. Ramping capability up to 45°. Improved chip evacuation due to central through-coolant. Due to the patented geometry also suitable for boring. With the latest generation of DLC coating  $sp^2$ . Advantage: Optimised flute form, eccentric relief ground, generous chip spaces. Tolerance nominal Ø: e8 No. of teeth Z: 3 Helix angle: 42 degrees Direction of infeed: horizontal, oblique and vertical Shank: DIN 6535 HA to h6 Balance quality with shank: G 2.5 with HA No. of teeth Z: 3 Flute length L<sub>c</sub>: 22 mm Overhang length L<sub>1</sub> incl. recess: 30 mm Recess Ø D<sub>1</sub>: 8.8 mm Overall length L: 72 mm Shank Ø D<sub>s</sub>: 10 mm

## **Technical description**

Flute length L <sub>c</sub>	22 mm
Shank	DIN 6535 HA to h6
Helix angle	42 degrees
Recess Ø D <sub>1</sub>	8.8 mm
Balance quality with shank	G 2.5 with HA
Overhang length L <sub>1</sub> incl. recess	30 mm
Cutting edge $Ø D_c$	9 mm
Shank Ø D <sub>s</sub>	10 mm
Tolerance nominal Ø	e8
Overall length L	72 mm
Feed $f_z$ for side milling in short-chipping aluminium	0.12 mm
Feed $f_z$ for slot milling in short-chipping aluminium	0.08 mm
Direction of infeed	horizontal, oblique and vertical
No. of teeth Z	3
Corner rounding r <sub>v</sub>	0.32 mm
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Туре	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Through-coolant	yes
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

# Services

© Hoffmann GmbH Qualitätswerkzeuge

Shank grinding Type HB

129100 HB