

Garant
GARANT Master Alu PickPocket solid carbide roughing end mill HPC, uncoated, Ø e8 DC: 8 mm

Order data

Order number	202012 8
GTIN	4062406126261
Item class	11X

Description
Version:

For roughing and finishing.

Up to 2×D into solid material at very high feed rates and smooth cutting action.

Very high feed rates when plunging vertically.

Ramping capability up to 45°.

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Note:

A minimum oversize of 0.1×D must be maintained for subsequent finishing operations.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 19 mm

Overhang length L_1 incl. recess: 30 mm

Recess Ø D_1 : 7.8 mm

Overall length L: 68 mm

Shank Ø D_s : 8 mm

Technical description

Recess Ø D_1	7.8 mm
----------------	--------

Balance quality with shank	G 2.5 with HA
Helix angle	42 degrees
Feed f_z for slot milling in short-chipping aluminium	0.05 mm
Tolerance nominal \varnothing	e8
Overall length L	68 mm
Shank $\varnothing D_s$	8 mm
Overhang length L_1 incl. recess	30 mm
Cutting edge $\varnothing D_c$	8 mm
Direction of infeed	horizontal, oblique and vertical
No. of teeth Z	3
Flute length L_c	19 mm
Shank	DIN 6535 HA to h6
Feed f_z for side milling in short-chipping aluminium	0.07 mm
Corner chamfer angle	90 degrees
Series	GARANT Master Alu
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB

129100 HB