

Garant

GARANT Master Alu PickPocket solid carbide roughing end mill HPC, DLC, Ø e6 DC: 16 mm



Order data

Order number	202017 16
GTIN	4062406381066
Item class	11X

Description

Version:

For roughing and finishing.

Up to 2×D into solid material at very high feed rates and smooth cutting action.

Very high feed rates when plunging vertically.

Ramping capability up to 45°.

Very long overhang for safe machining of deep cavities.

With the latest generation of DLC coating sp².

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Note:

A minimum oversize of 0.1×D must be maintained for subsequent finishing operations.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c: 25 mm

Overhang length L₁ incl. recess: 100 mm

Recess Ø D₁: 15 mm

Overall length L: 150 mm

Shank Ø D_s: 16 mm

Technical description

Balance quality with shank	G 2.5 with HA
Direction of infeed	horizontal, oblique and vertical
Overall length L	150 mm
Overhang length L ₁ incl. recess	100 mm
No. of teeth Z	3
Feed f _z for side milling in short-chipping aluminium	0.1 mm
Helix angle	42 degrees
Cutting edge Ø D _c	16 mm
Shank	DIN 6535 HA to h6
Feed f _z for slot milling in short-chipping aluminium	0.08 mm
Recess Ø D ₁	15 mm
Corner rounding r _v	0.2 mm
Shank Ø D _s	16 mm
Tolerance nominal Ø	e8
Flute length L _c	25 mm
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a _e for milling operation	0.3×D for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

