


Solid carbide mini milling cutter, uncoated, Ø e8 DC: 16 mm

Order data

Order number	202262 16
GTIN	4045197864246
Item class	12X

Description
Version:

Shank similar to **DIN 6535 HB**.

Save on regrinding costs:

It is cheaper to use solid carbide mini milling cutters to the wear limit than to regrind them.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: HB with h6

No. of teeth Z: 3

Flute length L_c : 18 mm

Overall length L: 65 mm

Shank Ø D_s : 16 mm

Shank form: HB

Feed f_z for slot milling in steel < 750 N/mm²: 0.08 mm

Technical description

Direction of infeed	horizontal, oblique and vertical
Shank form	HB
No. of teeth Z	3
Cutting edge Ø D_c	16 mm
Shank Ø D_s	16 mm

Overall length L	65 mm
Feed f_z for side milling in steel $< 750 \text{ N/mm}^2$	0.13 mm
Flute length L_c	18 mm
Shank	HB with h6
Feed f_z for slot milling in steel $< 750 \text{ N/mm}^2$	0.08 mm
Tolerance nominal \varnothing	e8
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm	SZ2025 16
---	-----------