


Garant**Solid carbide mini milling cutter, AlCrN, Ø e8 DC: 9 mm****Order data**

Order number	202265 9
GTIN	4045197930491
Item class	11X

Description**Version:**Shank similar to **DIN 6535 HB**.**Save on regrinding costs:**

It is cheaper to use solid carbide mini milling cutters to the wear limit than to regrind them.

Improved coating for general-purpose applications in steel and cast iron.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length L_c : 11 mm

Overall length L: 55 mm

Shank Ø D_s : 10 mm

Shank form: HB

Corner chamfer width at 45°: 0.1 mm

Technical description

Feed f_z for side milling in steel < 750 N/mm ²	0.08 mm
Overall length L	55 mm
Flute length L_c	11 mm
Cutting edge Ø D_c	9 mm
Shank	DIN 6535 HB to h6

Helix angle	45 degrees
Corner chamfer width at 45°	0.1 mm
Shank Ø D _s	10 mm
Shank form	HB
No. of teeth Z	3
Feed f _z for slot milling in steel < 750 N/mm ²	0.05 mm
Direction of infeed	horizontal, oblique and vertical
Tolerance nominal Ø	e8
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Cutting width a _e for milling operation	0.5×D for side milling
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill