


Solid carbide mini milling cutter, uncoated, Ø e8 DC: 10 mm

Order data

Order number	202266 10
GTIN	4045197864871
Item class	12X

Description
Version:

Shank similar to **DIN 6535 HB**.

Save on regrinding costs:

It is cheaper to use solid carbide mini milling cutters to the wear limit than to regrind them.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: HB with h6

No. of teeth Z: 3

Flute length L_c : 13 mm

Overall length L: 55 mm

Shank Ø D_s : 10 mm

Shank form: HB

Feed f_z for slot milling in steel < 750 N/mm²: 0.06 mm

Technical description

Flute length L_c	13 mm
Feed f_z for slot milling in steel < 750 N/mm ²	0.06 mm
Tolerance nominal Ø	e8
Feed f_z for side milling in steel < 750 N/mm ²	0.09 mm
Shank Ø D_s	10 mm
Cutting edge Ø D_c	10 mm

Overall length L	55 mm
Shank	HB with h6
No. of teeth Z	3
Shank form	HB
Direction of infeed	horizontal, oblique and vertical
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill