


**Solid carbide mini milling cutter, uncoated, Ø e8 DC: 6 mm**

**Order data**

Order number	202266 6
GTIN	4045197864796
Item class	12X

**Description**
**Version:**

Shank similar to **DIN 6535 HB**.

**Save on regrinding costs:**

It is cheaper to use solid carbide mini milling cutters to the wear limit than to regrind them.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: HB with h6

No. of teeth Z: 3

Flute length  $L_c$ : 8 mm

Overall length L: 45 mm

Shank Ø  $D_s$ : 6 mm

Shank form: HB

Feed  $f_z$  for slot milling in steel < 750 N/mm<sup>2</sup>: 0.04 mm

**Technical description**

No. of teeth Z	3
Tolerance nominal Ø	e8
Shank form	HB
Direction of infeed	horizontal, oblique and vertical
Flute length $L_c$	8 mm

Shank $\varnothing D_s$	6 mm
Shank	HB with h6
Feed $f_z$ for side milling in steel $< 750 \text{ N/mm}^2$	0.05 mm
Overall length L	45 mm
Feed $f_z$ for slot milling in steel $< 750 \text{ N/mm}^2$	0.04 mm
Cutting edge $\varnothing D_c$	6 mm
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Colour ring	without
Type of product	End mill