

Garant
Solid carbide milling cutter, AlCrN, Ø e8 DC: 9 mm

Order data

Order number	202267 9
GTIN	4045197865038
Item class	11X

Description
Version:

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 3

Flute length L_c : 19 mm

Overhang length L_1 incl. recess: 32 mm

Recess Ø D_1 : 8.8 mm

Overall length L: 72 mm

Shank Ø D_s : 10 mm

Technical description

No. of teeth Z	3
Shank	DIN 6535 HA to h6
Tolerance nominal Ø	e8
Overhang length L_1 incl. recess	32 mm
Shank Ø D_s	10 mm
Direction of infeed	horizontal, oblique and vertical

Cutting edge $\varnothing D_c$	9 mm
Overall length L	72 mm
Recess $\varnothing D_1$	8.8 mm
Flute length L_c	19 mm
Feed f_z for side milling in steel $< 750 \text{ N/mm}^2$	0.08 mm
Feed f_z for slot milling in steel $< 750 \text{ N/mm}^2$	0.05 mm
Helix angle	30 degrees
Corner chamfer angle	90 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------