

Garant**Solid carbide milling cutter MTC, DLC, Ø h6 DC: 12 mm****Order data**

Order number	202271 12
GTIN	4045197860132
Item class	11X

Description**Version:**

With the latest generation of **DLC coating sp²**.

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium components.

Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Note:

NEW GENERATION AVAILABLE!

Recommended successor product is No. 202014.

Tolerance nominal Ø: h6

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c: 26 mm

Overhang length L₁ incl. recess: 46 mm

Recess Ø D₁: 11 mm

Overall length L: 93 mm

Shank Ø D_s: 12 mm

Technical description

No. of teeth Z	3
Tolerance nominal Ø	h6

Corner chamfer width at 45°	0.2 mm
Direction of infeed	horizontal, oblique and vertical
Flute length L_c	26 mm
Shank $\varnothing D_s$	12 mm
Shank form	HA
Recess $\varnothing D_1$	11 mm
Overall length L	93 mm
Balance quality with shank	G 2.5 with HA
Overhang length L_1 incl. recess	46 mm
Feed f_z for side milling in short-chipping aluminium	0.07 mm
Feed f_z for slot milling in short-chipping aluminium	0.05 mm
Shank	DIN 6535 HA to h6
Cutting edge $\varnothing D_c$	12 mm
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

Services

SZ2025 12

Shank clamping flats for shrink-fit chucks, with retainer
function Shank Ø tool 12 mm

Shank grinding Type HB

129100 HB