Garant

GARANT Master Steel solid carbide mini milling cutter HPC, TiAIN, Ø e8 DC: 1,5 mm



Order data

Order number	202289 1,5
GTIN	4062406271107
Item class	11X

Description

Version:

Extra short cutter for maximum stability. **Shank length to DIN** for improved support of the tool in the holder. This significantly increases the tool life.

Save the regrinding costs: It is cheaper to use a carbide mini slot drill to the limit of wear and throw it away, than to regrind it.

Tool for **general-purpose machining.**

Note:

HB shanks are available at the same price as HA. For **HB** shanks use order **no. 202291**. Tolerance nominal \emptyset : e8 No. of teeth Z: 3 Helix angle: 30 degrees Direction of infeed: horizontal, oblique and vertical Shank: DIN 6535 HA to h6 No. of teeth Z: 3 Flute length L_c: 3 mm Overall length L_c: 3 mm Shank \emptyset D₃: 3 mm Feed f_z for slot milling in steel < 900 N/mm²: 0.005 mm Feed f_z for side milling in steel < 900 N/mm²: 0.006 mm

Technical description

Cutting edge $Ø D_c$

1.5 mm

e8
3 mm
horizontal, oblique and vertical
3
0.005 mm
30 degrees
DIN 6535 HA to h6
3 mm
38 mm
0.006 mm
90 degrees
GARANT Master Steel
TiAIN
Solid carbide
Manufacturer's standard
Ν
unequal spacing
Full slot cutting depth 1×D
Full slot cutting depth 1×D
no
HPC
green
End mill