

Garant
GARANT Master Steel solid carbide mini-milling cutter HPC, TiAlN, Ø e8 DC: 4,5 mm

Order data

Order number	202291 4,5
GTIN	4062406271572
Item class	11X

Description
Version:

Extra short cutter for maximum stability. **Shank length to DIN** for improved support of the tool in the holder. This significantly increases the tool life.

Save the regrinding costs: It is cheaper to use a carbide mini slot drill to the limit of wear and throw it away, than to regrind it.

Tool for **general-purpose machining**.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length L_c : 8 mm

Overall length L: 50 mm

Shank Ø D_s : 6 mm

Feed f_z for slot milling in steel < 900 N/mm²: 0.025 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.028 mm

Technical description

Tolerance nominal Ø	e8
Feed f_z for slot milling in steel < 900 N/mm ²	0.025 mm
Helix angle	30 degrees

Shank	DIN 6535 HB to h6
Overall length L	50 mm
Feed f_z for side milling in steel $< 900 \text{ N/mm}^2$	0.028 mm
Shank $\varnothing D_s$	6 mm
Direction of infeed	horizontal, oblique and vertical
Cutting edge $\varnothing D_c$	4.5 mm
Flute length L_c	8 mm
No. of teeth Z	3
Corner chamfer angle	90 degrees
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill