

Garant
Solid carbide milling cutter, AlCrN, Ø e8 DC: 5,5 mm

Order data

Order number	202292 5,5
GTIN	4045197866028
Item class	11X

Description
Version:

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 3

Flute length L_c : 13 mm

Overhang length L_1 incl. recess: 21 mm

Recess Ø D_1 : 5.3 mm

Overall length L: 57 mm

Shank Ø D_s : 6 mm

Technical description

Overall length L	57 mm
Shank	DIN 6535 HA to h6
Feed f_z for slot milling in steel < 750 N/mm ²	0.03 mm
Direction of infeed	horizontal, oblique and vertical
Shank Ø D_s	6 mm
Tolerance nominal Ø	e8

Cutting edge $\varnothing D_c$	5.5 mm
Feed f_z for side milling in steel $< 750 \text{ N/mm}^2$	0.04 mm
Flute length L_c	13 mm
No. of teeth Z	3
Overhang length L_1 incl. recess	21 mm
Recess $\varnothing D_1$	5.3 mm
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	$0.5 \times D$ for side milling
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------