

**Solid carbide milling cutter, AlCrN, Ø e8 DC: 7 mm****Order data**

Order number	202296 7
GTIN	4045197866431
Item class	12X

Description**Version:**

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length L_c : 16 mm

Overall length L: 63 mm

Shank Ø D_s : 8 mm

Corner chamfer width at 45°: 0.2 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.04 mm

Technical description

Tolerance nominal Ø	e8
Cutting edge Ø D_c	7 mm
Shank Ø D_s	8 mm
Overall length L	63 mm
Flute length L_c	16 mm
Corner chamfer width at 45°	0.2 mm

Feed f_z for slot milling in steel < 750 N/mm ²	0.04 mm
Feed f_z for side milling in steel < 750 N/mm ²	0.05 mm
Shank	DIN 6535 HB to h6
No. of teeth Z	3
Direction of infeed	horizontal, oblique and vertical
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill