

**Solid carbide milling cutter, uncoated, Ø e8 DC: 7,5 mm****Order data**

Order number	202307 7,5
GTIN	4062406093501
Item class	12X

Description**Version:**

Dimensions similar to **DIN 6527**.

Note:

Successor product to No. 202240 / 202245.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length L_c : 19 mm

Overall length L: 63 mm

Shank Ø D_s : 8 mm

Shank form: HB

Feed f_z for slot milling in steel < 750 N/mm²: 0.05 mm

Technical description

Direction of infeed	horizontal, oblique and vertical
Helix angle	45 degrees
Shank form	HB
Cutting edge Ø D_c	7.5 mm
Feed f_z for slot milling in steel < 750 N/mm ²	0.05 mm

Shank	DIN 6535 HB to h6
Overall length L	63 mm
Shank Ø D _s	8 mm
Flute length L _c	19 mm
Tolerance nominal Ø	e8
Feed f _z for side milling in steel < 750 N/mm ²	0.07 mm
No. of teeth Z	3
Corner chamfer angle	90 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width a _e for milling operation	0.5×D for side milling
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill