

**Garant**
**Solid carbide milling cutter MTC, AlCrN, Ø f8 DC: 4 mm**

**Order data**

Order number	202391 4
GTIN	4062406270810
Item class	11X

**Description**
**Version:**

**Special flute profile. Strengthened core.**

**MTC rough milling up to 1.5×D in solid material.**

**Eccentric relief ground.**

Particularly sturdy due to short overall length. Overall length similar to **DIN 6527 short.**

**Application:**

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Tolerance nominal Ø: f8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length  $L_c$ : 8 mm

Overhang length  $L_1$  incl. recess: 15 mm

Recess Ø  $D_1$ : 3.8 mm

Overall length L: 54 mm

Shank Ø  $D_s$ : 6 mm

**Technical description**

Flute length $L_c$	8 mm
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.024 mm
Tolerance nominal Ø	f8

Balance quality with shank	G 2.5 with HA
Shank	DIN 6535 HA to h6
Helix angle	45 degrees
Recess $\varnothing D_1$	3.8 mm
Overall length L	54 mm
Corner chamfer width at 45°	0.08 mm
Direction of infeed	horizontal, oblique and vertical
Overhang length $L_1$ incl. recess	15 mm
Shank $\varnothing D_s$	6 mm
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.02 mm
No. of teeth Z	3
Cutting edge $\varnothing D_c$	4 mm
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	green
Type of product	End mill